

SPECIALIZED PUMP COMPANY, INC.

"IN BUSINESS SINCE 1972"

P.O. Box 3805 HOLLYWOOD, FLORIDA 33083 PHONE (954) 967-2071 FAX (954) 967-2074
WWW.SPECIALIZEDPUMP.COM

ROTO-FLOAT OPTION LIST

ROTO-FLOAT SYSTEM STANDARD FEATURES

- Audible Alarm - A horn will acknowledge any alarm condition
- External Silencer Button - External Nema 4X silencer button
- Alternation of Pumps
- Red Warning Light - on top of the control panel illuminates in conjunction with the warning alarm.
- Underwriters Labs (UL) Listed and approved (E130708)

ROTO-FLOAT CONTROL PANEL OPTION LIST

- AC Line Surge Protection
 - Lightning Arrestor
 - Elapsed Time Meter Each Pump
 - Phase Monitor
 - Intrinsically Safe
 - Mechanical Seal Failure Protection for the Pumps
 - Temperature Protection Terminals for the Pumps
 - Emergency Generator Connection
 - Main Disconnect
 - Dry Contacts: Use for Remote Alarm Annunciation
 - Duplex Receptacle 110VAC: G.F.I. 110 V.A.C. Outlet in Panel
 - Power On Light**
 - Level Indicating Lights**
 - Aluminum Inner Door
- Enclosures Choices:
- Steel (Standard)
 - Fiberglass
 - Stainless Steel

(**Requires Inner Door Option)

ROTO-FLOAT SYSTEM ACCESSORY LIST

- Basin: Fiberglass Poly Standard Anti-Float Size: _____
- Basin Lids: Steel Aluminum Poly Standard Traffic Bearing Size: _____
- Door-Hatch Simplex Duplex
- Slide Rails For Submersible Pumps Size: _____
- Guide Pipes: Stainless Steel - Custom Cut Lengths Quantity: _____
Size: _____
- Floats: Normally Open Normally Closed Quantity: _____
 Cord Lengths from 20 to 100 Feet Length: _____
 Weights
 Float Holder (Stainless Steel):
- Lifting Mechanisms: Chain-Stainless Steel
 Cables-Stainless Steel
- Valve Box Fiberglass Size: _____